

1454 LED

STANDARD SPECIFICATIONS

HOUSING

Assembled from formed, cold rolled steel, this simple design is a classic look that blends with any décor.

MOUNT PAN

Manufactured using cold rolled steel with a baked on, high reflectance white finish.

DIFFUSER

The front diffuser ranges from the understated look of basic white, to a selection of fabrics and color options. The side panels are constructed from quality white acrylic.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 548 lm. Non-dimming.
B12 - 12W nominal, .10 A input - 1084 lm. Dimmable (0-10V).
C09 - 9W nominal, .10 A input - 764 lm. Dimmable (0-10V).
C17 - 16W nominal, .15 A input - 1566 lm. Dimmable (0-10V).
C24 - 23W nominal, .20 A input - 2148 lm. Dimmable (0-10V).
C37 - 35W nominal, .30 A input - 4380 lm. Dimmable (0-10V).

MOUNTING

The 1454 is designed to be mounted directly to a j-box (by others).
The 27" version has additional holes for anchor bolts (by others) appropriate for the mounting surface.

FINISH

The 1454 series is available in all Brownlee paint finishes as a standard offering.


WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



NT finish, WHA diffuser



DAMP



ORDERING INFORMATION

1454 - Model - 2. - 3. - 4. - 5. - 6. - 7. (if required)

2. SIZE	3. FINISH	4. WATTAGE	5. DIFFUSER	6. COLOR TEMPERATURE
15 L: 15"	STANDARD	15 SIZE	STANDARD	35K 3500K standard color temperature
27 L: 27"	AB Antique Bronze	B06 6W B Series LED	WHA White Acrylic	27K 2700K color temperature
	AS Antique Silver	B12 12W B Series LED		30K 3000K color temperature
	BL Black		OPTIONAL	40K 4000K color temperature
	BZ Bronze	C09 9W C Series LED	BMB Bamboo	
	DB Desert Bronze	C17 16W C Series LED	BLU Blue	
	GM Gun Metal	C24 23W C Series LED	GYL Grey Linen	
	MB Metallic Bronze		LMG Lime Green	
	MG Metallic Gold	27 SIZE	LRD Light Red	
	NT Nickel Tone	C37 35W C Series LED	NAL Natural Linen	
	PL Platinum		ORN Orange	
	WH White		WBK Woven Black	
	CUSTOM		WHL White Linen	
	Provide color sample or RAL code to match			
			*NOTE: GDM, MAL, PER, ROW, & SAP have been discontinued from this model - contact factory for availability.	
				7. AVAILABLE OPTIONS
				90R⁰ 90 CRI (3000K only)
				BAC¹ Buy American Compliant
				DTR⁴ Triac (Line Voltage) Dimming (120V) (All except B06)
				ES⁶ ENERGY STAR® (Not available in 90 CRI)
				FCL⁷ French Canadian Labels
				T24⁹ Title 24 Compliant (B12 & C24 in 3000K only)

Notes: (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.



REVISED
2020.05.19