

1456 LED

STANDARD SPECIFICATIONS

HOUSING

Assembled from formed, cold rolled steel, the straightforward nature of the half-cylinder is a timeless style that is never out of place.

MOUNT PAN

Manufactured using cold rolled steel with a baked on, high reflectance white finish.

DIFFUSER

The rounded diffuser can be specified in solid white acrylic, or, one of our fabrics or color options which are sheilded by a clear acrylic outer lens, creating a cleanable surface.

LED PERFORMANCE - 3500K STANDARD

120-277V, 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 527 lm. Non-dimming.
B12 - 12W nominal, .10 A input - 1042 lm. Dimmable (0-10V).
C09 - 9W nominal, .10 A input - 735 lm. Dimmable (0-10V).
C17 - 16W nominal, .15 A input - 1506 lm. Dimmable (0-10V).
C24 - 23W nominal, .20 A input - 2066 lm. Dimmable (0-10V).
C37 - 35W nominal, .30 A input - 3064 lm. Dimmable (0-10V).

MOUNTING

The 1456 is designed to be mounted directly to a j-box (by others). The 25" version has additional holes for anchor bolts (by others) appropriate for the mounting surface.

FINISH

The 1456 series is available in all Brownlee paint finishes as a standard offering.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION

1456 - Model - 2. - 3. - 4. - 5. - 6. - 7. (if required)

2. SIZE	3. FINISH	4. WATTAGE	5. DIFFUSER	6. COLOR TEMPERATURE
13 L: 13"	STANDARD	13 SIZE	STANDARD	35K 3500K standard color temperature
25 L: 25"	AB Antique Bronze	B06 6W B Series LED	WHA White Acrylic	27K 2700K color temperature
	AS Antique Silver	B12 12W B Series LED	OPTIONAL	30K 3000K color temperature
	BL Black	C09 9W C Series LED	BMB Bamboo	40K 4000K color temperature
	BZ Bronze	C17 16W C Series LED	BLU Blue	
	DB Desert Bronze	C24 23W C Series LED	GYL Grey Linen	7. AVAILABLE OPTIONS
	GM Gun Metal		LMG Lime Green	90R⁰ 90 CRI (3000K only)
	MB Metallic Bronze		LRD Light Red	BAC¹ Buy American Compliant
	MG Metallic Gold		NAL Natural Linen	DTR⁴ Triac (Line Voltage) Dimming (120V) (All except B06)
	NT Nickel Tone	25 SIZE	ORN Orange	ES⁶ ENERGY STAR® (Not available in 90 CRI)
	PL Platinum	C37 35W C Series LED	WBK Woven Black	FCL⁷ French Canadian Labels
	WH White		WHL White Linen	T24⁹ Title 24 Compliant (B12 & C24 in 3000K only)
	CUSTOM			
	Provide color sample or RAL code to match			

Notes: (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.


Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

PROJECT:
MODEL #:
FIXTURE TYPE:



NT finish, WHA diffuser



DAMP

