

2069

STANDARD SPECIFICATIONS

SHADE

The shade is constructed from traditional lampshade material with a polyethylene liner, wrapped around a steel frame. It is available in multiple materials, divided into two pricing tiers.

TRIM

Cold rolled steel stem and canopy

HOUSING

Formed, cold rolled steel design, finished in a high reflectance powder coat white.

ELECTRICAL

T5 Linear Fluorescent, bipin lamp (by others) - 120-277V Electronic HPF Ballast
T5HO Linear Fluorescent, bipin lamp (by others) - 120-277V Electronic HPF Ballast

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 2069 series is available in all Brownlee paint finishes as a standard offering.

PROJECT:
MODEL #:
FIXTURE TYPE:



ORDERING INFORMATION

2069

Model 2. 3. 4. 5. (if required)

2. FINISH

STANDARD

BL	Black
BT	Brass Tone
BZ	Bronze
GM	Gun Metal
MB	Metallic Bronze
NT	Nickel Tone
PL	Platinum
WH	White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

314L	3-14W T5, elec. HPF
324L	3-24W T5HO, elec. HPF

4. DIFFUSER

TIER 1

SN1	Satin Weave - White
SN2	Satin Weave - Ivory
SN3	Satin Weave - Aurora Gold

BP1 Burlap - Ivory

TIER 2

SS1	Silk Shantung - White
SS2	Silk Shantung - Cream
SS3	Silk Shantung - Taupe
SP3	Genuine Silk Pongee - Natural
GR1	Grasscloth - Natural
BK1	Black Percale

5. AVAILABLE OPTIONS

BAC	Buy American Compliant
SVL	Swivel Canopy / Slope Ceiling
TBC	Top and Bottom Cover

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.