

2126

STANDARD SPECIFICATIONS

PAN

The classic decorative layered look in a 20 GA cold rolled steel spinning.

DIFFUSER

Formed glass, with a faux alabaster finish and an etched outer surface that softens the light. The diffuser is held in place by a cold rolled steel check ring, and a solid brass ball finial.

ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp – 120-277V Electronic HPF Ballast
 GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 2126 series is finished in either electroplated brush nickel or high reflectance white powder coat. Also available in all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

ORDERING INFORMATION

2126 - _____
 Model 2. 3. 4. 5. (if required)

PROJECT:
MODEL #:
FIXTURE TYPE:



2. SIZE

13 13" dia.
15 15" dia.

3. FINISH

BN **STANDARD**
 Brushed Nickel

OPTIONAL

BL Black
BZ Bronze
GM Gun Metal
MB Metallic Bronze
MG Metallic Gold
NT Nickel Tone
PL Platinum
WH White

CUSTOM

Provide color sample or RAL code to match

4. WATTAGE

13 SIZE

13Q 1-13W Quad CFL, elec. HPF
213Q 2-13W Quad CFL, elec. HPF
18Q 1-18W Quad CFL, elec. HPF
218Q 2-18W Quad CFL, elec. HPF
26Q 1-26W Quad CFL, elec. HPF

13G 1-13W GU24 CFL, elec. NPF
213G 2-13W GU24 CFL, elec. NPF
18G 1-18W GU24 CFL, elec. NPF
218G 2-18W GU24 CFL, elec. NPF

15 SIZE

213Q 2-13W Quad CFL, elec. HPF
313Q 3-13W Quad CFL, elec. HPF
218Q 2-18W Quad CFL, elec. HPF
26Q 1-26W Quad CFL, elec. HPF
226Q 2-26W Quad CFL, elec. HPF

213G 2-13W GU24 CFL, elec. NPF
313G 3-13W GU24 CFL, elec. NPF
218G 2-18W GU24 CFL, elec. NPF

5. AVAILABLE OPTIONS

BAC Buy American Compliant
BBI¹ Integral Battery Backup (Q only, 15 size only)
DIM1 Dimming Ballast (120V) (Q only)
DIM2 Dimming Ballast (277V) (Q only)
ES ENERGY STAR® (26Q & 226Q only)
OCC² Occupancy Sensor
 13 size - 1 lamp only
 15 size - 2 lamp max

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

2) Occupancy sensor operates with microwaves and is not recommended for use in waiting areas with elevators.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.