

2300

STANDARD SPECIFICATIONS

TRIM

Molded, sturdy polyurethane decorative ring, painted in any of the standard Brownlee finishes.

DIFFUSER

Translucent, UV stabilized white acrylic, injection molded in the familiar puff shape with a uniform thickness throughout. The diffuser is held in position with spring loaded clips.

PAN

Steel, die-formed construction with formed ring to keep the surface off the wall, and finished in a high reflectance white powder coat.

ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp – 120-277V Electronic HPF Ballast
GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 2300 is available in all Brownlee paint finishes as a standard offering.

PROJECT:

MODEL #:



FIXTURE TYPE:



BZ finish



NT finish



DAMP



ORDERING INFORMATION

2300

Model

2.

3.

4.

5. (if required)

2. SIZE

17 17" dia.
21 21.5" dia

3. FINISH

STANDARD

BL Black
BZ Bronze
GM Gun Metal
MB Metallic Bronze
MG Metallic Gold
NT Nickel Tone
PL Platinum
WH White

CUSTOM

Provide color sample or RAL code to match

4. WATTAGE

17 SIZE

213Q 2-13W Quad CFL, elec. HPF
218Q 2-18W Quad CFL, elec. HPF
226Q 2-26W Quad CFL, elec. HPF

213G 2-13W GU24 CFL, elec. NPF
313G 3-13W GU24 CFL, elec. NPF
218G 2-18W GU24 CFL, elec. NPF

21 SIZE

313Q 3-13W Quad CFL, elec. HPF
413Q 4-13W Quad CFL, elec. HPF
218Q 2-18W Quad CFL, elec. HPF
318Q 3-18W Quad CFL, elec. HPF
226Q 2-26W Quad CFL, elec. HPF
326Q 3-26W Quad CFL, elec. HPF

313G 3-13W GU24 CFL, elec. NPF
413G 4-13W GU24 CFL, elec. NPF
218G 2-18W GU24 CFL, elec. NPF
318G 3-18W GU24 CFL, elec. NPF

5. AVAILABLE OPTIONS

BAC Buy American Compliant
DIM1 Dimming Ballast (120V) (Q only)
DIM2 Dimming Ballast (277V)(Q only)
ES ENERGY STAR® (226Q & 326Q only)

ACCESSORIES (field installed)

BBR¹ Remote Battery Backup (Q only)
BBRC¹ Remote Battery Backup, Cold Weather (Q only)

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.