

2414

STANDARD SPECIFICATIONS

HOUSING

Cold rolled steel, formed and assembled with welds and hardware, and bolted to the pan. The frame is 20 GA, ensuring a rugged, damage resistant housing.

DIFFUSER

UV stabilized white acrylic panels held in position with construction tabs welded inside the housing.

PAN

Formed, cold rolled steel design, finished in a high reflectance white powder coat.

ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp – 120-277V Electronic HPF Ballast

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.


FINISH

The 2414 series is available in all Brownlee paint finishes as a standard offering.

PROJECT:
MODEL #:
FIXTURE TYPE:



GM finish



DAMP



ORDERING INFORMATION

2414 - Model - 2. - 3. - 4. - 5. (if required)

2. SIZE

- 10 10.5" sq.
- 13 13.5" sq.

3. FINISH

STANDARD

- AB** Antique Bronze
- AS** Antique Silver
- BL** Black
- BZ** Bronze
- DB** Desert Bronze
- GM** Gun Metal
- MB** Metallic Bronze
- MG** Metallic Gold
- NT** Nickel Tone
- PL** Platinum
- WH** White

CUSTOM

Provide color sample or RAL code to match

4. WATTAGE

10 SIZE

- 13Q** 1-13W Quad CFL, elec. HPF
- 213Q** 2-13W Quad CFL, elec. HPF
- 18Q** 1-18W Quad CFL, elec. HPF

13 SIZE

- 213Q** 2-13W Quad CFL, elec. HPF
- 18Q** 1-18W Quad CFL, elec. HPF
- 218Q** 2-18W Quad CFL, elec. HPF
- 26Q** 1-26W Quad CFL, elec. HPF
- 226Q** 2-26W Quad CFL, elec. HPF

5. AVAILABLE OPTIONS

- BAC** Buy American Compliant
- DIM1** Dimming Ballast (120V)
- DIM2** Dimming Ballast (277V)
- ES** ENERGY STAR® (26Q & 226Q only)

ACCESSORIES (field installed)

- BBR¹** Remote Battery Backup
- BBRC¹** Remote Battery Backup, Cold Weather

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

2) Occupancy sensor operates with microwaves and is not recommended for use in waiting areas with elevators.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.