

7156

STANDARD SPECIFICATIONS

HOUSING

Injection molded polycarbonate, one piece housing with a uniform .08" thickness. The color is molded throughout and features drill pads for side conduit entry.

DIFFUSER

UV stabilized white polycarbonate, injection molded with a thickness of .08". The inside top of the diffuser is molded with small prisms to disguise the light source.

REFLECTOR

Cold rolled steel finished with a powder coat high reflectance white finish

ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp - 120-277V Electronic HPF Ballast

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included. Not available with conduit entry.

FINISH

Brownlee offers two standard molded finishes.


PROJECT:
MODEL #:
FIXTURE TYPE:



WH finish



BL finish



WET



ORDERING INFORMATION

7156 - - - -
 Model 2. 3. 4. (if required)

2. FINISH

BL Black
WH White

3. WATTAGE

13Q 1-13W Quad CFL, elec. HPF
213Q 2-13W Quad CFL, elec. HPF
18Q 1-18W Quad CFL, elec. HPF
218Q 2-18W Quad CFL, elec. HPF
26Q 1-26W Quad CFL, elec. HPF

4. AVAILABLE OPTIONS

BAC Buy American Compliant
DIM1 Dimming Ballast (120V)
DIM2 Dimming Ballast (277V)
ES ENERGY STAR® (26Q only)
OCC² Occupancy Sensor* (1 lamp only)

ACCESSORIES (field installed)

BBR¹ Remote Battery Backup
BBRC¹ Remote Battery Backup, Cold Weather

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

2) Occupancy sensor operates with microwaves and is not recommended for use in waiting areas with elevators.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.