

# 7326 LED

## STANDARD SPECIFICATIONS

### HOUSING

Cold rolled steel, formed and assembled with welds and hardware, and bolted to the pan. The end caps and cupolas are 20 GA, ensuring a rugged, damage resistant housing. This fixture is not recommended for installation along coastal areas. Contact factory for further details.

### DIFFUSER

UV stabilized white acrylic, formed into a "U" shape and held in position with construction tabs welded inside the housing.

### PAN

Formed, cold rolled steel design, finished in a high reflectance white powder coat.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
 Amperage rated @ 110V input  
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Standard 3500K source lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 700 lm - 117 lm/W. Non-dimming.  
 B12 - 12W nominal, .10 A input - 1430 lm - 123 lm/W. Dimmable (0-10V).  
 C09 - 9W nominal, .10 A input - 1200 lm - 144 lm/W. Dimmable (0-10V).  
 C17 - 16W nominal, .15 A input - 2050 lm - 132 lm/W. Dimmable (0-10V).  
 C24 - 23W nominal, .20 A input - 2950 lm - 131 lm/W. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The 7326 series is available in all Brownlee paint finishes as a standard offering.

### WARRANTY


5 year limited warranty on this LED product. Consult factory for details.

### ORDERING INFORMATION

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



BL finish



WET



## 7326

Model                    2.                    3.                    4.                    5. (if required)

### 2. FINISH

#### STANDARD

<b>AB</b>	Antique Bronze
<b>AS</b>	Antique Silver
<b>BL</b>	Black
<b>BZ</b>	Bronze
<b>DB</b>	Desert Bronze
<b>GM</b>	Gun Metal
<b>MB</b>	Metallic Bronze
<b>NT</b>	Nickel Tone
<b>PL</b>	Platinum
<b>WH</b>	White

#### CUSTOM

Provide color sample or RAL code to match

### 3. WATTAGE

<b>B06</b>	6W B Series LED
<b>B12</b>	12W B Series LED
<b>C09</b>	9W C Series LED
<b>C17</b>	16W C Series LED
<b>C24</b>	23W C Series LED

### 4. COLOR TEMPERATURE

<b>35K</b>	3500K standard color temperature
<b>27K</b>	2700K color temperature
<b>30K</b>	3000K color temperature
<b>40K</b>	4000K color temperature

### 5. AVAILABLE OPTIONS

<b>BAC<sup>1</sup></b>	Buy American Compliant
<b>DTR<sup>4</sup></b>	Triac (Line Voltage) Dimming (120V) (All except B06)
<b>ECW<sup>5</sup></b>	Extreme Cold Weather (-40°C / -40°F min.)
<b>ES<sup>6</sup></b>	ENERGY STAR®
<b>FCL<sup>7</sup></b>	French Canadian Labels
<b>OCC<sup>8</sup></b>	Occupancy Sensor
<b>T24<sup>9</sup></b>	Title 24 Compliant (B12 & C24 in 3000K only)

**Notes:** (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, DTR, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 cannot be combined with BLD or OCC

**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.