





7600 LED-

The 7600 series (Models: 7600/01/02/04/10/12/14/16) is available in a variety of sizes and lumen packages, making it highly versatile for exterior facades. Constructed of aluminum with your choice of durable powder coat finish, sturdy acrylic diffuser, and stainless steel hardware. Use this architectural sconce for any application requiring performance and a decorative aesthetic. Perfect for exterior facades, columns, breezeways, pool decks, and more. Vertical bars optional. Integral battery backup and cold weather integral battery backup optional.

FINISHES





PRO-22 | H4

STANDARD SPECIFICATIONS

Heavy duty aluminum with roll formed aluminum bands. The optional trim bars are solid 0.250" thick aluminum, held in place by fasteners.

DIFFUSER

Translucent, UV stabilized, white acrylic. Diffuser is form molded allowing for a uniform standard thickness of 0.100" throughout.

PAN

Heavy duty formed aluminum, featuring aluminum thread inserts to prevent rusting

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 50°C / 122°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

C24 - 23W nominal, .20 A input - 2110 lm. Dimmable (0-10V).

C49 - 45W nominal, .40 A input - 4219 lm. Dimmable (0-10V).

MOUNTING

The 7600 series is designed to be mounted directly to the wall with (4) 1/4" anchors (not

FINISH

All 7600 parts are prepared using a three step pre-treatment/sealing process, followed by a powder coat primer prior to applying any of the Brownlee paint finishes.

WARRANTY

7600

5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION

PROJECT: MODEL #: FIXTURE TYPE:



*Note: For a proportionally 22' smaller size, refer to Model #: 7601 LED.





6. (if required)







Wodel 2.	J	5.	o. (ii required)
2. FINISH	3. WATTAGE	4. TRIM	5. COLOR TEMPERATURE
STANDARD BL Black BZ Bronze GM Gun Metal MB Metallic Bronze NT Nickel Tone WH White	C24 23W C Series LEDC49 45W C Series LED	VB0 No trim VB1 1 vertical bar VB2 2 vertical bars	35K 3500K standard color temperature 27K 2700K color temperature 30K 3000K color temperature 40K 4000K color temperature 6. AVAILABLE OPTIONS
CUSTOM Provide color sample or RAL code to match			BAB¹ Build America, Buy America Compliant (BABAA) (Exclusions: BBI, BBC) BAC¹ Buy American Compliant (BAA) Integral Battery Backup (8W) (adds 1.5" to depth) BBC²* Integral Battery Backup, Cold Weather (16W) (adds 1.5" to depth) Battery must be connected to continuous power supply within 7 Mo. of shipping. See Warranty. Note 3. BLD³** Bi-Level Dimming DTR⁴ Triac (Line Voltage) Dimming (120V) ECW⁵ Extreme Cold Weather (-40°C / -40°F min.) EXT Extended Housing (Intended to match BBI (C) aesthetic) (Adds 1.5" to depth) FCL¹ French Canadian Labels OCC³ Occupancy Sensor T24° Title 24 IA8 Compliant (3000K only)



