



Brushed Nickel (BN) | FL1 diffuser



Brushed Nickel (BN) | RD2 diffuser

2061 LED

The modern SPIN features high efficacy performance and is perfect for corridors, units and plenty of other general lighting applications. Twist-lock diffuser design with two styles to choose from and no exposed hardware. Refer to the 2081 for a similar look offered in larger sizes.

SPIN

STANDARD SPECIFICATIONS

HOUSING

Cold rolled 20 GA steel, formed with die punch tooling with no exposed hardware. The pan has three steel brackets which mate with the diffuser. Reveal (RVL) option available: 3/4" decorative extension collar lifts the luminaire from the mounting surface to accentuate its shape and create a floating effect with a subtle shadow.

DIFFUSER

Translucent, UV stabilized, white acrylic. Diffuser is vacuum formed and features a secure "twist lock" tool free installation method.

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B12 - 12W nominal, .10 A input - 980 lm. Dimmable (0-10V).

C17 - 16W nominal, .15 A input - 1415 lm. Dimmable (0-10V).

C24 - 23W nominal, .20 A input - 1940 lm. Dimmable (0-10V).


PROJECT:

MODEL #:


FIXTURE TYPE:



Brushed Nickel (BN) | RD2 diffuser



RD2 diffuser



FL1 diffuser

ORDERING INFORMATION



DAMP



2061

Model

2.

3.

4.

5.

6. (if required)

2. FINISH

STANDARD

BN Brushed Nickel

OPTIONAL

BL Black
BZ Bronze
GM Gun Metal
MB Metallic Bronze
MG Metallic Gold
NT Nickel Tone
PL Platinum
WH White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

B12 12W B Series LED

C17 16W C Series LED

C24 23W C Series LED

4. DIFFUSER

FL1 Style 1 Flat Diffuser

RD2 Style 2 Round Diffuser

*Note: RD1 has been discontinued

5. COLOR TEMPERATURE

35K 3500K standard color temperature

27K 2700K color temperature

30K 3000K color temperature

40K 4000K color temperature

6. AVAILABLE OPTIONS

90R⁰ 90 CRI (3000K only)

BAC¹ Buy American Compliant

BLD^{3**} Bi-Level Dimming

DTR⁴ Triac (Line Voltage) Dimming (120V)

ES⁶ ENERGY STAR[®] (Not available in 90 CRI)

FCL⁷ French Canadian Labels

OCC⁸ Occupancy Sensor

RVL Reveal (Matches selected finish) (Adds 3/4" to height)

T24⁹ Title 24 JA8 Compliant (B12 & C24 in 3000K only)

Notes: (0) 90R - cannot be combined with ES. (1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24.

(3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24.

(5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24.

(8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI,

BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC.

Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating

temperature of -20C/-4F. **BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50%

(factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.



BROWNLEE
LIGHTING

www.brownlee.com

REVISED
2021.08.17