# **FULTON**





# 2454 LED -

The 2454 LED close-to-ceiling pendant pairs nicely with the 2654 LED traditional pendant and the two models are often used in the same space. This series offers a balance between traditional and contemporary, making it perfect for a variety of spaces from lobbies and entryways to foyers and corridors in applications such as libraries, schools, hotels and more. This unit provides a generous amount of indirect uplight in addition to downlight.

# **FINISHES**





# **FULTON**

### STANDARD SPECIFICATIONS

#### BOW

Smooth UV stabilized white acrylic. The  $24^{\prime\prime}$  bowl is formed from  $0.188^{\prime\prime}$  material, while the  $30^{\prime\prime}$  bowl utilizes  $0.250^{\prime\prime}$  stock.

#### TRIM

The trim consists of a formed, cold rolled steel ceiling canopy, stainless steel aircraft cables, three solid brass finials, and a steel stem.

#### **HOUSING**

Formed, cold rolled steel design, finished in a high reflectance powder coat white.

#### **LED PERFORMANCE - 3500K STANDARD**

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

C24 - 23W nominal, .20 A input - 2958 lm. Dimmable (0-10V). C37 - 35W nominal, .30 A input - 4460 lm. Dimmable (0-10V).

C49 - 45W nominal, .40 A input - 5916 lm. Dimmable (0-10V).

#### **MOUNTING**

Directly to j-box (by others). Mounting hardware included.

#### **FINISH**

The 2454 series is available in all Brownlee paint finishes as a standard offering.


#### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.





NT finish





## ORDERING INFORMATION

	<b>2454</b> Model		<b>2</b> .	3.	4.		5. 6. (if required)		
2.	SIZE	3.	FINISH	4.	WATTAGE	5.	COLOR TEMPERATURE	6.	AVAILABLE OPTIONS
24 30	24" dia. 30" dia.		STANDARD  Black Bronze Gun Metal Metallic Bronze Metallic Gold Nickel Tone Platinum White  CUSTOM ide color sample or code to match	C24 C37 C49 C37 C49	24 SIZE 23W C Series LED 35W C Series LED 45W C Series LED 30 SIZE 35W C Series LED 45W C Series LED	35K 27K 30K 40K	3500K standard color temperature 2700K color temperature 3000K color temperature 4000K color temperature	90R <sup>0</sup> BAC <sup>1</sup> BLD <sup>3</sup> DTR <sup>4</sup> ES <sup>6</sup> FCL <sup>7</sup> OCC <sup>8</sup>	Buy American Compliant Bi-Level Dimming Triac (Line Voltage) Dimming (120V) ENERGY STAR® (Not available in 90 CRI) French Canadian Labels

Notes: (0) 90R - cannot be combined with ES.1) BAC - cannot be combined with FCL. (2) BBI/BBS/BBC - cannot be combined with ECW, EXT, or T24. (3) BLD - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) DTR - cannot be combined with BLD or T24. (5) ECW - cannot be combined with BBI, BBC, or DTR. (6) ES - cannot be combined with 90R or T24. (7) FCL - cannot be combined with BAC or T24. (8) OCC - integral ON/OFF occupancy sensor. (9) T24 - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) BBS - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) PCH/PC4 - cannot be combined with BLD or OCC. Add'l Notes: \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of 20C/4F. \*\*BLD - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

