

LUMIBOX

STANDARD SPECIFICATIONS

HOUSING

Assembled from formed, cold rolled steel, this simple design is a classic look that blends with any décor.

MOUNT PAN

Manufactured using cold rolled steel with a baked on, high reflectance white finish.

DIFFUSER

The front diffuser ranges from the understated look of basic white, to a selection of fabrics and color options. The side panels are constructed from quality white acrylic.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 548 lm. Non-dimming.
B12 - 12W nominal, .10 A input - 1084 lm. Dimmable (0-10V).
C09 - 9W nominal, .10 A input - 764 lm. Dimmable (0-10V).
C17 - 16W nominal, .15 A input - 1566 lm. Dimmable (0-10V).
C24 - 23W nominal, .20 A input - 2148 lm. Dimmable (0-10V).
C37 - 35W nominal, .30 A input - 4380 lm. Dimmable (0-10V).

MOUNTING

The 1454 is designed to be mounted directly to a j-box (by others).
The 27" version has additional holes for anchor bolts (by others) appropriate for the mounting surface.

FINISH

The 1454 series is available in all Brownlee paint finishes as a standard offering.


WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



NT finish, WHA diffuser



ORDERING INFORMATION

1454 - Model - 2. - 3. - 4. - 5. - 6. - 7. (if required)

2. SIZE	3. FINISH	4. WATTAGE	5. DIFFUSER	6. COLOR TEMPERATURE
15 L: 15"	STANDARD AB Antique Bronze AS Antique Silver BL Black BZ Bronze DB Desert Bronze GM Gun Metal MB Metallic Bronze MG Metallic Gold NT Nickel Tone PL Platinum WH White CUSTOM Provide color sample or RAL code to match	15 SIZE B06 6W B Series LED B12 12W B Series LED C09 9W C Series LED C17 16W C Series LED C24 23W C Series LED 27 SIZE C37 35W C Series LED	STANDARD WHA White Acrylic OPTIONAL BMB Bamboo BLU Blue GYL Grey Linen LMG Lime Green LRD Light Red NAL Natural Linen ORN Orange WBK Woven Black WHL White Linen	35K 3500K standard color temperature 27K 2700K color temperature 30K 3000K color temperature 40K 4000K color temperature
27 L: 27"		7. AVAILABLE OPTIONS 90R⁰ 90 CRI (3000K only) BAC¹ Buy American Compliant DTR⁴ Triac (Line Voltage) Dimming (120V) (All except B06) ES⁶ ENERGY STAR® (Not available in 90 CRI) FCL⁷ French Canadian Labels T24⁹ Title 24 Compliant (B12 & C24 in 3000K only)		

Notes: (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

