

# SPAN

## STANDARD SPECIFICATIONS

### HOUSING

Assembled from formed, cold rolled steel, the straightforward nature of the half-cylinder is a timeless style that is never out of place.

### MOUNT PAN

Manufactured using cold rolled steel with a baked on, high reflectance white finish.

### DIFFUSER

The rounded diffuser can be specified in solid white acrylic, or, one of our fabrics or color options which are sheilded by a clear acrylic outer lens, creating a cleanable surface.

### LED PERFORMANCE - 3500K STANDARD

120-277V, 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
Amperage rated @ 110V input  
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B06 - 6W nominal, .05 A input - 527 lm. Non-dimming.  
B12 - 12W nominal, .10 A input - 1042 lm. Dimmable (0-10V).  
C09 - 9W nominal, .10 A input - 735 lm. Dimmable (0-10V).  
C17 - 16W nominal, .15 A input - 1506 lm. Dimmable (0-10V).  
C24 - 23W nominal, .20 A input - 2066 lm. Dimmable (0-10V).  
C37 - 35W nominal, .30 A input - 3064 lm. Dimmable (0-10V).

### MOUNTING

The 1456 is designed to be mounted directly to a j-box (by others). The 25" version has additional holes for anchor bolts (by others) appropriate for the mounting surface.

### FINISH

The 1456 series is available in all Brownlee paint finishes as a standard offering.


### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

|                      |
|----------------------|
| <b>PROJECT:</b>      |
| <b>MODEL #:</b>      |
| <b>FIXTURE TYPE:</b> |



NT finish, WHA diffuser



## ORDERING INFORMATION



DAMP



**1456** - Model - 2. - 3. - 4. - 5. - 6. - 7. (if required)

| 2. SIZE      | 3. FINISH  | 4. WATTAGE  | 5. DIFFUSER  | 6. COLOR TEMPERATURE  |
|--------------|--|---|--|---|
| 13<br>L: 13" | <b>STANDARD</b><br><b>AB</b> Antique Bronze<br><b>AS</b> Antique Silver<br><b>BL</b> Black<br><b>BZ</b> Bronze<br><b>DB</b> Desert Bronze<br><b>GM</b> Gun Metal<br><b>MB</b> Metallic Bronze<br><b>MG</b> Metallic Gold<br><b>NT</b> Nickel Tone<br><b>PL</b> Platinum<br><b>WH</b> White<br><br><b>CUSTOM</b><br>Provide color sample or RAL code to match | <b>13 SIZE</b><br><b>B06</b> 6W B Series LED<br><b>B12</b> 12W B Series LED<br><br><b>C09</b> 9W C Series LED<br><b>C17</b> 16W C Series LED<br><b>C24</b> 23W C Series LED<br><br><b>25 SIZE</b><br><b>C37</b> 35W C Series LED  | <b>STANDARD</b><br><b>WHA</b> White Acrylic<br><br><b>OPTIONAL</b><br><b>BMB</b> Bamboo<br><b>BLU</b> Blue<br><b>GYL</b> Grey Linen<br><b>LMG</b> Lime Green<br><b>LRD</b> Light Red<br><b>NAL</b> Natural Linen<br><b>ORN</b> Orange<br><b>WBK</b> Woven Black<br><b>WHL</b> White Linen<br><br>*NOTE: GDM, MAL, PER, ROW, & SAP have been discontinued from this model - contact factory for availability. | <b>35K</b> 3500K standard color temperature<br><b>27K</b> 2700K color temperature<br><b>30K</b> 3000K color temperature<br><b>40K</b> 4000K color temperature |
| 25<br>L: 25" |  | <b>7. AVAILABLE OPTIONS</b><br><b>90R<sup>0</sup></b> 90 CRI (3000K only)<br><b>BAC<sup>1</sup></b> Buy American Compliant<br><b>DTR<sup>4</sup></b> Triac (Line Voltage) Dimming (120V) (All except B06)<br><b>ES<sup>6</sup></b> ENERGY STAR® (Not available in 90 CRI)<br><b>FCL<sup>7</sup></b> French Canadian Labels<br><b>T24<sup>9</sup></b> Title 24 Compliant (B12 & C24 in 3000K only) |  |   |

**Notes:** (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

