

# 1562

## STANDARD SPECIFICATIONS

### HOUSING

Cold rolled steel, roll formed and assembled using a series of spot welds and hardware. Multiple interior braces provide rigidity and stability. The housing has a perforated cover as a standard feature.

### DIFFUSER

Translucent, UV stabilized white acrylic. The material is flexible to withstand minor impact without breaking. Available in multiple hand painted finishes and a selection of fabrics and distinctive patterns.

### PAN

Formed, cold rolled steel design, finished with a powder coat high reflectance white paint.

### ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp – 120-277V Electronic HPF Ballast  
 GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

### MOUNTING

Directly to j-box (by others). Mounting hardware included.


### FINISH

The 1562 series is available in all Brownlee paint finishes as a standard offering. It is also available in an optional electroplated brushed nickel. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



BN finish, WA diffuser



**DAMP**



## ORDERING INFORMATION

**1562** - \_\_\_\_\_  
 Model                      2.                      3.                      4.

### 2. FINISH

#### STANDARD

- AB** Antique Bronze
- AS** Antique Silver
- BL** Black
- BZ** Bronze
- DB** Desert Bronze
- GM** Gun Metal
- MB** Metallic Bronze
- MG** Metallic Gold
- NT** Nickel Tone
- PL** Platinum
- WH** White

#### OPTIONAL

- BN** Brushed Nickel

#### CUSTOM

Provide color sample or RAL code to match

### 3. WATTAGE

- 13Q** 1-13W Quad CFL, elec. HPF
- 213Q** 2-13W Quad CFL, elec. HPF
- 18Q** 1-18W Quad CFL, elec. HPF
- 218Q** 2-18W Quad CFL, elec. HPF
- 26Q** 1-26W Quad CFL, elec. HPF
- 226Q** 2-26W Quad CFL, elec. HPF
  
- 13G** 1-13W GU24 CFL, elec. NPF
- 18G** 1-18W GU24 CFL, elec. NPF

### 4. AVAILABLE OPTIONS

- BAC** Buy American Compliant
- DIM1** Dimming Ballast (120V) (Q only)
- DIM2** Dimming Ballast (277V) (Q only)
- ES** ENERGY STAR® (26Q & 226Q only)

#### ACCESSORIES (field installed)

- BBR'** Remote Battery Backup (Q only)

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.