

2020

STANDARD SPECIFICATIONS

FRAME

Injection molded, black polycarbonate frame designed to resist impact and cold weather. The frame is installed on the pan with hardware.

DIFFUSER

Translucent, UV stabilized 0.080" frosted acrylic panel assembly.

PAN

Formed, cold rolled steel design, with a zinc galvanized finish to resist corrosion.

ELECTRICAL

Quad CFL, 4-pin G24q Base 2700K lamp - 120-277V Electronic HPF Ballast
GU24 CFL, 2-prong Base 2700K lamp - 120V Electronic NPF Ballast


Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.

PROJECT:
MODEL #:
FIXTURE TYPE:



ORDERING INFORMATION

2020 - _____ - _____
 Model 2. 3. (if required)

2. WATTAGE

13Q	1-13W Quad CFL, elec. HPF
213Q	2-13W Quad CFL, elec. HPF
18Q	1-18W Quad CFL, elec. HPF
218Q	2-18W Quad CFL, elec. HPF
26Q	1-26W Quad CFL, elec. HPF
13G	1-13W GU24 CFL, elec. NPF
213G	2-13W GU24 CFL, elec. NPF
18G	1-18W GU24 CFL, elec. NPF
218G	2-18W GU24 CFL, elec. NPF

3. AVAILABLE OPTIONS

BAC	Buy American Compliant
ES	ENERGY STAR® (26Q only)
T	Tamper Resistant Hardware and Tool

ACCESSORIES (field installed)

BBR¹	Remote Battery Backup (Q only)
BBRC¹	Remote Battery Backup, Cold Weather (Q only)

1) BBI & BBR options have an operating temperature of +32°F to +122°F. BBIC & BBRC options have an operating temperature of -4°F to +131°F. BBR & BBRC are field installed options available on all HPF fluorescent (CFL & T8) fixtures, except those with dimming ballasts. The maximum distance between the battery and the fixture is 10' for HPF ballasts.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.