

# SHADER SHALLOW

## STANDARD SPECIFICATIONS

### SHADE

The shade is constructed from traditional lampshade material with a polyethylene liner, wrapped around a steel frame. It is available in multiple materials, divided into two pricing tiers.

### TRIM

Cold rolled steel stem and canopy, and additional aircraft cable accents. The lower cover is held in place with a solid brass finial. All trim pieces available in all Brownlee paint finishes.

### DIFFUSER

A white acrylic cover is located on both the top and the bottom of the shade.

### HOUSING

Formed, cold rolled steel design, finished in a high reflectance powder coat white.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs

Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

3500K delivered lumens noted. Consult Brownlee.com for performance of all CCTs.

C49 - 45W nominal, .40 A input - 4265 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The 2066 series is available in all Brownlee paint finishes as a standard offering.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION


**2066** - \_\_\_\_\_  
 Model                      2.                      3.                      4.                      5.                      6.                      7. (if required)

2. SIZE	3. FINISH	4. WATTAGE	5. DIFFUSER	6. COLOR TEMPERATURE
<b>20</b> 20" dia.	<b>STANDARD</b>	<b>C49</b> 45W C Series LED	<b>TIER 1</b>	<b>35K</b> 3500K standard color temperature
<b>24</b> 24" dia.	<b>BL</b> Black		<b>SN1</b> Satin Weave - White	<b>27K</b> 2700K color temperature
	<b>BZ</b> Bronze		<b>SN2</b> Satin Weave - Ivory	<b>30K</b> 3000K color temperature
	<b>GM</b> Gun Metal		<b>TIER 2</b>	<b>40K</b> 4000K color temperature
	<b>MB</b> Metallic Bronze		<b>GR1</b> Grasscloth - Natural	
	<b>MG</b> Metallic Gold		<b>BK1</b> Black Linen	
	<b>NT</b> Nickel Tone			
	<b>PL</b> Platinum			
	<b>WH</b> White			
	<b>CUSTOM</b>			
	Provide color sample or RAL code to match			
				<b>7. AVAILABLE OPTIONS</b>
				<b>90R<sup>0</sup></b> 90 CRI (3000K only)
				<b>BAC<sup>1</sup></b> Buy American Compliant
				<b>DTR<sup>4</sup></b> Triac (Line Voltage) Dimming (120V)
				<b>ES<sup>6</sup></b> ENERGY STAR® (Not available in 90 CRI)
				<b>FCL<sup>7</sup></b> French Canadian Labels
				<b>T24<sup>9</sup></b> Title 24 Compliant (3000K only)

<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



BL finish, GR1 diffuser



**DAMP**



### ACCESSORIES (field installed - order separately)

**390001xx** SCM Extension Kit: includes (1) 1' stem and (2) 2' stems. 5' combined max. Specify finish (xx)

**Notes:** (0) **90R** - cannot be combined with ES or T24 (1) **BAC** - cannot be combined with FCL (2) **BBI/BBS/BBC** - cannot be combined with DTR, ECW, EXT, or T24 (3) **BLD** - cannot be combined with DTR, OCC, or T24 (4) **DTR** - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) **ECW** - cannot be combined with BBI, BBC, or DTR (6) **ES** - cannot be combined with 90R, FCL, or T24 (7) **FCL** - cannot be combined with BAC, ES, or T24 (8) **OCC** - cannot be combined with BLD (9) **T24** - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) **BBS** - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) **PCH/PC4** - cannot be combined with BLD or OCC

**Add'l Notes:** \***BBI/BBS/BBC** - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\***BLD** - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.

