FAUXNUT SURFACE







2326 LED -

Since it's not quite a donut, we've nicknamed this series the "fauxnut."

The one-piece 2326 is constructed of a matte white acrylic outer shell with a flat, inset diffuser opening. Available in a matte white acrylic or woven black fabric diffuser. Integral Battery Backup available on 15" & 20" sizes.

Refer to model 2616 for a suspended version of this product.



FAUXNUT SURFACE

STANDARD SPECIFICATIONS

Cold rolled 22 GA steel, formed in a die, finished in a powder coat high reflectance white paint. The pan features weld nuts for a "twist and hold" installation of the diffuser.

DIFFUSER

The drum features a high quality UV stabilized white acrylic outer shell. The base (bottom) of the drum features an inset section and is constructed with high transmission white acrylic. The fixture can be cleaned with a damp cloth and mild detergent if needed.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs Amperage rated @ 110V input

Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

15 Size: R11 - 11W nominal, .09 A input - 1619 lm. Dimmable (0-10V). 15 Size: R18 - 18W nominal, .15 A input - 2588 lm. Dimmable (0-10V) 15 Size: R22 - 22W nominal, .19 A input - 3050 lm. Dimmable (0-10V). 20 Size: R23 - 23W nominal, .19 A input - 2977 lm. Dimmable (0-10V). 20 Size: R34 - 34W nominal, .28 A input - 4387 lm. Dimmable (0-10V). 20 Size: R49 - 49W nominal, .41 A input - 5828 lm. Dimmable (0-10V). 24 Size: R23 - 23W nominal, .19 A input - 3102 lm. Dimmable (0-10V). 24 Size: R34 - 34W nominal, .28 A input - 4569 lm. Dimmable (0-10V). 24 Size: R49 - 49W nominal, .41 A input - 6071 lm. Dimmable (0-10V). 30 Size: R23 - 23W nominal, .19 A input - 2954 lm. Dimmable (0-10V).

30 Size: R34 - 34W nominal, .28 A input - 4352 lm. Dimmable (0-10V). 30 Size: R49 - 49W nominal, .41 A input - 5782 lm. Dimmable (0-10V).

^{*}Testing performed on White Acrylic shade option. WBK fabric decreases lumen output.



Directly to j-box (by others). Sizes 24"+ are further anchored to ceiling at three points for additional support (anchoring hardware by others).

2326

Model

5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION

2. SIZE WATTAGE 15 15" dia. 15 SIZE 20 19.25" dia. **R11** 11W R Series LED 24 24" dia. **R18** 18W R Series LED 30" dia. **R22** 22W R Series LED

	20,	24, 30 SIZE
R23		23W R Series LED
R34		34W R Series LED
R49		49W R Series LED

White Acrylic WHA 35K **WBK** Woven Black 27K 30K 40K

5.

DIFFUSER

3000K color temperature 4000K color temperature

3500K standard color temperature 2700K color temperature

COLOR TEMPERATURE AVAILABLE OPTIONS 6.

6. (if required)

90R⁰ 90 CRI (30K & 35K only) BAC1 BBI2*

DTR⁴

ES⁶

EXT

T249

Buy American Compliant Integral Battery Backup (8W) (Adds 1.5" to depth (15 & 20 sizes only) Battery must be connected to continuous power supply

within 7 Mo. of shipping. See Warranty Note 3. Triac (Line Voltage) Dimming (120V) ENERGY STAR® (Not available in 90 CRI) Extended Housing (Intended to match BBI

extension) (Adds 1.5" to depth) (15 & 20 sizes only)

FCL7 French Canadian Labels

Title 24 JA8 Compliant (30K & 35K only)

PROJECT: MODEL #: FIXTURE TYPE:











