

# BREEZE-RD

## STANDARD SPECIFICATIONS

### PAN

Cold rolled steel, formed in a die, finished with an electroplated brushed nickel coating that will withstand most nicks and scratches.

### DIFFUSER

Translucent, UV stabilized white acrylic with optional White Linen fabric material bonded to the walls, allowing for ease of cleaning with a dry or damp cloth.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
Amperage rated @ 110V input  
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

B12 - 12W nominal, .10 A input - 1414 lm. Dimmable (0-10V).  
C17 - 16W nominal, .15 A input - 2043 lm. Dimmable (0-10V).  
C24 - 23W nominal, .20 A input - 2803 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.

### FINISH

The standard finish is a sturdy electroplated brushed nickel. Options include all Brownlee paint finishes. Plated finishes such as Brushed Nickel are suitable for indoor applications only. Installation outdoors voids the Brownlee Limited Warranty.

### WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

## ORDERING INFORMATION

**2335** - \_\_\_\_\_  
Model                      2.                      3.                      4.                      5.                      6. (if required)

### 2. FINISH

**STANDARD**  
**BN**    Brushed Nickel

**OPTIONAL**  
**BL**    Black  
**BZ**    Bronze  
**GM**    Gun Metal  
**MB**    Metallic Bronze  
**MG**    Metallic Gold  
**NT**    Nickel Tone  
**PL**    Platinum  
**WH**    White

**CUSTOM**  
Provide color sample or RAL code to match

### 3. WATTAGE

**B12**    12W B Series LED  
**C17**    16W C Series LED  
**C24**    23W C Series LED

### 4. DIFFUSER

**WHA**    White Acrylic  
**WHL**    White Linen

### 5. COLOR TEMPERATURE

**35K**    3500K standard color temperature  
**27K**    2700K color temperature  
**30K**    3000K color temperature  
**40K**    4000K color temperature

### 6. AVAILABLE OPTIONS

**90R<sup>0</sup>**    90 CRI (3000K only)  
**BAC<sup>1</sup>**    Buy American Compliant  
**BLD<sup>3\*\*</sup>**    Bi-Level Dimming  
**DTR<sup>4</sup>**    Triac (Line Voltage) Dimming (120V)  
**ES<sup>5</sup>**    ENERGY STAR® (Not available in 90 CRI)  
**FCL<sup>7</sup>**    French Canadian Labels  
**OCC<sup>8</sup>**    Occupancy Sensor  
**T24<sup>9</sup>**    Title 24 JA8 Compliant (B12 & C24 in 3000K only)


<b>PROJECT:</b>
<b>MODEL #:</b>
<b>FIXTURE TYPE:</b>



BN finish, WHA diffuser



BZ finish, WHL diffuser



**DAMP**



**Notes:** (0) **90R** - cannot be combined with ES. (1) **BAC** - cannot be combined with FCL. (2) **BBI/BBS/BBC** - cannot be combined with ECW, EXT, or T24. (3) **BLD** - includes integral OCC sensor (do not combine with OCC option). Cannot be combined with DTR or T24. (4) **DTR** - cannot be combined with BLD or T24. (5) **ECW** - cannot be combined with BBI, BBC, or DTR. (6) **ES** - cannot be combined with 90R or T24. (7) **FCL** - cannot be combined with BAC or T24. (8) **OCC** - integral ON/OFF occupancy sensor. (9) **T24** - includes JA8 labeling and 90 CRI LEDs (do not combine with 90R option). Cannot be combined with BBI, BBC, BBS, BLD, DTR, ES, or FCL. (10) **BBS** - cannot be combined with BLD, ECW, EXT, OCC, or T24. (11) **PCH/PC4** - cannot be combined with BLD or OCC.  
**Add'l Notes:** \***BBI/BBS/BBC** - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\***BLD** - integral OCC sensor with onboard control. 1: Motion is detected, illuminate to 100%. 2: Motion no longer detected, dim to 50% (factory default), 30%, 20% or 10%. 3: Remain in continuous dimmed state (factory default) or turn off after set period.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.