

7140

STANDARD SPECIFICATIONS

PAN

Formed aluminum design, finished in a powder coat high reflectance white paint.

DIFFUSER

Injection molded clear prismatic polycarbonate, UV stabilized material that is resistant to damage due to the 0.085" base thickness. The diffuser features a painted bronze cutoff to control light distribution.

ELECTRICAL


GU24 CFL, 2-prong Base 2700K lamp – 120V Electronic NPF Ballast

Brownlee Lighting does not recommend GU24 base lamps for 24 hour operation due to lamp manufacturer specifications.

Fluorescent fixtures utilizing an occupancy sensor should include a programmed start HPF ballast. Fluorescent lamps powered by instant start or rapid start ballasts, or GU24 base compact fluorescent lamps used in this application may result in severely shortened lamp life and/or ballast damage.

MOUNTING

Directly to j-box (by others). Mounting hardware included.



| |
|---------------|
| PROJECT: |
| MODEL #: |
| FIXTURE TYPE: |

ORDERING INFORMATION



DAMP **WET**
(optional)

7140 - _____ - _____
Model 2. 3. (if required)

2. WATTAGE

13G 1-13W GU24 CFL, elec. NPF
18G 1-18W GU24 CFL, elec. NPF

3. AVAILABLE OPTIONS

BAC Buy American Compliant
T Tamper Resistant Hardware and Tool
W Wet Location

Specifications and dimensions subject to change without notice.
Consult your Brownlee Lighting representative for availability and ordering information.