

# GABLE

## STANDARD SPECIFICATIONS

### HOUSING

The classic wall lantern design is produced from a die-cast aluminum mold. The black powder coat finish is suitable for almost any environment.

### PAN

Formed from steel, the mount pan is finished with a sturdy powder coat white.

### DIFFUSER

UV stabilized, white acrylic panels held in place with clips.

### LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs  
 Amperage rated @ 110V input  
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.  
 B06 - 6W nominal, .05 A input - 543 lm. Non-dimming.  
 C09 - 9W nominal, .10 A input - 758 lm. Dimmable (0-10V).  
 C13 - 13W nominal, .10 A input - 1031 lm. Dimmable (0-10V).

### MOUNTING

Directly to j-box (by others). Mounting hardware included.


### WARRANTY

3 year limited warranty on this LED product. Consult factory for details.

PROJECT:
MODEL #:
FIXTURE TYPE:



PO1 option



WET



## ORDERING INFORMATION

**7322** - \_\_\_\_\_ - \_\_\_\_\_ - \_\_\_\_\_  
 Model                      2.                      3.                      4. (if required)

### 2. WATTAGE

- B06**    6W B Series LED
- C09**    9W C Series LED
- C13**    13W Series LED

### 3. COLOR TEMPERATURE

- 35K**    3500K standard color temperature
- 27K**    2700K color temperature
- 30K**    3000K color temperature
- 40K**    4000K color temperature

### 4. AVAILABLE OPTIONS

- BAC<sup>1</sup>**    Buy American Compliant
- DTR<sup>4</sup>**    Triac (Line Voltage) Dimming (120V) All except B06
- ES<sup>6</sup>**     ENERGY STAR<sup>®</sup>
- FCL<sup>7</sup>**    French Canadian Labels
- PO1**     Photo Control (120V)
- PO2**     Photo Control (208, 240, 277V)
- T24<sup>9</sup>**    Title 24 Compliant (C13 in 3000K only)

**Notes:** (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

**Add'l Notes:** \*BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. \*\*BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

### Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.