

HAVANA [TRIM]

STANDARD SPECIFICATIONS

HOUSING

Cold rolled steel, formed and assembled with welds and hardware, and bolted to the pan. The end caps and cupolas are 20 GA, ensuring a rugged, damage resistant housing. This fixture is not recommended for installation along coastal areas. Contact factory for further details.

DIFFUSER

UV stabilized white acrylic, formed into a "U" shape and held in position with construction tabs welded inside the housing.

PAN

Formed, cold rolled steel design, finished in a high reflectance white powder coat.

LED PERFORMANCE - 3500K STANDARD

120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
 Amperage rated @ 110V input
 Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.

- B06 - 6W nominal, .05 A input - 340 lm. Non-dimming.
- B12 - 12W nominal, .10 A input - 671 lm. Dimmable (0-10V).
- C09 - 9W nominal, .10 A input - 473 lm. Dimmable (0-10V).
- C17 - 16W nominal, .15 A input - 970 lm. Dimmable (0-10V).
- C24 - 23W nominal, .20 A input - 1331 lm. Dimmable (0-10V).

MOUNTING

Directly to j-box (by others). Mounting hardware included.

FINISH

The 7325 series is available in all Brownlee paint finishes as a standard offering.

WARRANTY

5 year limited warranty on this LED product. Consult factory for details.

ORDERING INFORMATION

7325 - - - - -
 Model 2. 3. 4. 5. (if required)

2. FINISH

STANDARD

- AB** Antique Bronze
- BL** Black
- BZ** Bronze
- DB** Desert Bronze
- GM** Gun Metal
- MB** Metallic Bronze
- NT** Nickel Tone
- PL** Platinum
- WH** White

CUSTOM

Provide color sample or RAL code to match

3. WATTAGE

- B06** 6W B Series LED
- B12** 12W B Series LED
- C09** 9W C Series LED
- C17** 16W C Series LED
- C24** 23W C Series LED

4. COLOR TEMPERATURE

- 35K** 3500K standard color temperature
- 27K** 2700K color temperature
- 30K** 3000K color temperature
- 40K** 4000K color temperature


5. AVAILABLE OPTIONS

- BAC¹** Buy American Compliant
- DTR⁴** Triac (Line Voltage) Dimming (120V) (All except B06)
- ECW⁵** Extreme Cold Weather (-40°C / -40°F min.)
- ES⁶** ENERGY STAR®
- FCL⁷** French Canadian Labels
- OCC⁸** Occupancy Sensor
- T24⁹** Title 24 Compliant (B12 & C24 in 3000K only)

PROJECT:
MODEL #:
FIXTURE TYPE:



BL finish



WET



Notes: (0) 90R - cannot be combined with ES or T24 (1) BAC - cannot be combined with FCL (2) BBI/BBS/BBC - cannot be combined with DTR, ECW, EXT, or T24 (3) BLD - cannot be combined with DTR, OCC, or T24 (4) DTR - cannot be combined with BBI, BBC, BBS, BLD or T24 (5) ECW - cannot be combined with BBI, BBC, or DTR (6) ES - cannot be combined with 90R, FCL, or T24 (7) FCL - cannot be combined with BAC, ES, or T24 (8) OCC - cannot be combined with BLD (9) T24 - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL (10) BBS - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 (11) PCH/PC4 - cannot be combined with BLD or OCC

Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. **BLD - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

Specifications and dimensions subject to change without notice.

Consult your Brownlee Lighting representative for availability and ordering information.