HAVANA

PROJECT:	
MODEL #:	
FIXTURE TYPE:	

STANDARD SPECIFICATIONS

HOUSING
Cold rolled steel, formed and assembled with welds and hardware, and bolted to the pan. The end caps and cupolas are 20 GA, ensuring a rugged, damage resistant housing. This fixture is not recommended for installation along coastal areas. Contact factory for further details.

DIFFUSER
UV stabilized white acrylic, formed into a "U" shape and held in position with construction tabs welded inside the housing.

PAN
Formed, cold rolled steel design, finished in a high reflectance white powder coat.

LED PERFORMANCE - 3500K STANDARD
120-277V - 3500K, 82 CRI - L80 rating - 60,000 hrs - L70 rating (projected) - 100,000 hrs
Amperage rated @ 110V input
Operating ambient temperature: -20°C / -4°F - 40°C / 104°F

Delivered 3500K lumens noted. Consult Brownlee.com for performance of all CCTs.
B06 - 6W nominal, .05 A input - 340 lm. Non-dimming.
B12 - 12W nominal, .10 A input - 671 lm. Dimmable (0-10V).
C09 - 9W nominal, .10 A input - 473 lm. Dimmable (0-10V).
C17 - 16W nominal, .15 A input - 970 lm. Dimmable (0-10V).
C24 - 23W nominal, .20 A input - 1331 lm. Dimmable (0-10V).

MOUNTING
Directly to j-box (by others). Mounting hardware included.

FINISH
The 7326 series is available in all Brownlee paint finishes as a standard offering.

WARRANTY
5 year limited warranty on this LED product. Consult factory for details.

BL finish



WET

SUPPORTS T24 COMPLIANCE

ORDERING INFORMATION

7326	-	_____	-	_____	-	_____	-	_____
Model		2.		3.		4.		5. (if required)

2. FINISH

STANDARD

AB	Antique Bronze
AS	Antique Silver
BL	Black
BZ	Bronze
DB	Desert Bronze
GM	Gun Metal
MB	Metallic Bronze
NT	Nickel Tone
PL	Platinum
WH	White

CUSTOM
Provide color sample or RAL code to match

3. WATTAGE

B06	6W B Series LED
B12	12W B Series LED
C09	9W C Series LED
C17	16W C Series LED
C24	23W C Series LED

4. COLOR TEMPERATURE

35K	3500K standard color temperature
27K	2700K color temperature
30K	3000K color temperature
40K	4000K color temperature

5. AVAILABLE OPTIONS

BAC[1]	Buy American Compliant
DTR[4]	Triac (Line Voltage) Dimming (120V) (All except B06)
ECW[5]	Extreme Cold Weather (-40°C / -40°F min.)
ES[6]	ENERGY STAR®
FCL[7]	French Canadian Labels
OCC[8]	Occupancy Sensor
T24[9]	Title 24 Compliant (B12 & C24 in 3000K only)

Notes: (0) 90R - cannot be combined with ES or T24 **(1) BAC** - cannot be combined with FCL **(2) BBI/BBS/BBC** - cannot be combined with DTR, ECW, EXT, or T24 **(3) BLD** - cannot be combined with DTR, OCC, or T24 **(4) DTR** - cannot be combined with BBI, BBC, BBS, BLD or T24 **(5) ECW** - cannot be combined with BBI, BBC, or DTR **(6) ES** - cannot be combined with 90R, FCL, or T24 **(7) FCL** - cannot be combined with BAC, ES, or T24 **(8) OCC** - cannot be combined with BLD **(9) T24** - cannot be combined with 90R, BBI, BBC, BBS, BLD, DTR, ES, or FCL **(10) BBS** - cannot be combined with BLD, DTR, ECW, EXT, OCC, or T24 **(11) PCH/PC4** - cannot be combined with BLD or OCC
Add'l Notes: *BBI/BBS/BBC - standard BBI (and BBS) option has a minimum operating temperature of 10C/50F. BBC option has a minimum operating temperature of -20C/-4F. ****BLD** - Bi-Level Dimming is field adjustable from 100% to a dimmed light level of 10, 20, 30, or 50%. All units are factory set at 50%.

Specifications and dimensions subject to change without notice.
Consult your Brownlee Lighting representative for availability and ordering information.

BROWNLEE LIGHTING
www.brownlee.com

REVISED 2020.09.28